



GP77



- Mixed service tire with cut and chip resistant tread compound for on/off road applications;
- Steel belted for tread stability and casing durability;
- Strong wear resistance, low heat generation.

Long Haul Regional On/Off Road Recommended

SIZE	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure			Overall Diameter	Section Width	Tread Depth		
					Dual	Single	Single					
11R22.5	16	146/143	M	8.25	2725	830	3000	830	1054	279.0	15.1	19
11R24.5	16	149/146	L	8.25	3000	830	3250	830	1104.0	279.0	16.7	21



GP515



- Improved tread pattern minimizes the heat generation, reinforced shoulders fight against irregular wear;
- Increased durability due to wide tread surface and rubber compound;
- Deep tread depth delivers extended usage, and lowers the cost per mile.

Long Haul Regional On/Off Road Recommended

SIZE	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure			Overall Diameter	Section Width	Tread Depth		
					Dual	Single	Single					
315/80R22.5	20	161/154	J	9.00	3750	850	3625	850	1076	312	16.5	21



GP616



- Deep, and compacted channels for better water dissipation, surface tread designed for long life circle;
- Improved rubber compound delivers heat control, and lowers overall abrasion wear;
- Zig-zag positioned center ribs for enhanced traction and braking characteristics.

Long Haul Regional On/Off Road Recommended

SIZE	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure			Overall Diameter	Section Width	Tread Depth		
					Dual	Single	Single					
385/65R22.5	20	160	J	11.75	-	-	4500	900	1072	389	15.5	20



GRIPower

GRIPower

TRUCK & BUS
TIRES CATALOG



Long Haul / Regional / Urban / On/Off Road / Recommended / Acceptable

GP888

- Unique Design gives longer mileage and better durability for any road conditions;
- Large blocks with 3D-kerf ensure traction capabilities in all weather conditions;
- New tread compound enhances dispersion and fuel efficiency.

SIZE	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure			Overall Diameter	Section Width	Tread Depth	Tread Depth	
					kg	lbs	PSI					
295/75R22.5	14	144/141	L	9.00	2650	720	2800	720	1020.0	298.0	21.4	27
295/75R22.5	16	146/143	L	9.00	2725	830	3000	830	1020.0	298.0	21.4	27
11R22.5	14	144/142	M	8.25	2725	720	3000	720	1059.0	279.0	21.4	27
11R22.5	16	146/143	M	8.25	3000	830	3250	830	1059.0	279.0	21.4	27
11R24.5	14	146/143	L	8.25	2575	760	2800	760	1110.0	279.0	21.4	27
11R24.5	16	149/146	L	8.25	2800	830	3075	830	1110.0	279.0	21.4	27
285/75R24.5	14	144/141	L	8.25	2725	830	3000	830	1056.0	283.0	22.5	28
285/75R24.5	16	147/144	L	8.25	2725	830	3000	830	1056.0	283.0	22.5	28

GP66



- Premium all-position steel radial highway service.
- Five-Rib tread design for premium handling and long life.
- Specially designed for steer axles and all-position usage.

SIZE	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure			Overall Diameter	Section Width	Tread Depth	Tread Depth	
					kg	lbs	PSI					
295/75R22.5	14	144/141	L	9.00	2650	720	2800	720	1014.0	298.0	14.3	18
295/75R22.5	16	146/143	L	9.00	2725	830	3000	830	1014.0	298.0	14.3	18
11R22.5	14	144/142	M	8.25	2725	720	3000	720	1054.0	279.0	14.3	18
11R22.5	16	146/143	M	8.25	3000	830	3250	830	1054.0	279.0	14.3	18
11R24.5	14	146/143	L	8.25	2575	760	2800	760	1104.0	279.0	14.3	18
11R24.5	16	149/146	L	8.25	2800	830	3075	830	1104.0	279.0	14.3	18
285/75R24.5	14	144/141	L	8.25	2725	830	3000	830	1050.0	283.0	15.1	19
285/75R24.5	16	147/144	L	8.25	2725	830	3000	830	1050.0	283.0	15.1	19
255/70R22.5	16	140/137	M	7.50	2300	830	2500	830	930.0	255.0	15.1	19

GP99



- Closed shoulder design promotes uniform wear, strong carcass promotes tire durability and tire retreading.
- Aggressive center lugs promote traction in all conditions, variable zigzag groove reduces groove crack;
- Optimized footprint for long tire circle, low rolling resistance.

SIZE	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure			Overall Diameter	Section Width	Tread Depth	Tread Depth	
					kg	lbs	PSI					
295/75R22.5	14	144/141	L	9.00	2650	720	2800	720	1020.0	298.0	21.4	27
295/75R22.5	16	146/143	L	9.00	2725	830	3000	830	1020.0	298.0	21.4	27

GRIPPOWER

GP818



- Drive pattern, high-density transverse grooves provide good anti-skid performance and suit for snow road;
- Special tread compound keeps rubber softness in low temperature, offer excellent grip;
- M+S pattern, with good traction performance and long mileage service.

SIZE	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure			Overall Diameter	Section Width	Tread Depth	Tread Depth	
					kg	lbs	PSI					
225/70R19.5	14	128/126	M	6.75	1700	760	1800	760	815	226	15.5	20
245/70R19.5	16	136/134	M	7.50	2060	830	2180	830	843	249	16	20

GP106



- Reinforced sidewalls fight against impacts when used as trailer application.
- Durable shoulder design helps maintain even wearing under high scrub driving conditions;
- Carefully engineered grooves and sipes to maximize.

SIZE	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure			Overall Diameter	Section Width	Tread Depth	Tread Depth	
					kg	lbs	PSI					
225/70R19.5	14	128/126	M	6.75	1700	760	1800	760	811	226	13.5	17
245/70R19.5	16	135/133	M	7.50	2120	850	2240	850	839	248	14.5	18
235/75R17.5	16	143/141	L	6.75	2500	850	2575	850	797	233	14.5	18
235/75R17.5	18	143/141	L	6.75	2575	875	2725	875	797	233	14.5	18

GP101



- Deep grooves provide good controlling for all terrain types;
- Rubber compound for low hear generating, abrasion resistance tread for better tread wear;
- Designed for spread axle, low flatbeds, and specialty trailers.

SIZE	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure			Overall Diameter	Section Width	Tread Depth	Tread Depth	
					kg	lbs	PSI					
215/75R17.5	16	135/133	L	6.00	1600	830	1750	830	767	211	12.5	16
215/75R17.5	18	135/133	L	6.00	2060	860	2180	860	797	233	12.5	16